



PRIME EXPOSURE SAME DAY SEALER

DESCRIPTION

Same Day Sealer is a penetrating, breathable primer coating designed for “same day” application on freshly poured concrete. The solvent-based acrylic is a ready for use sealer that can be applied directly to green curing concrete. It retains a wet/semi-gloss appearance, it also minimises substrate preparation and protects the surface whilst not allowing efflorescence rise through it. Prime sealers are UV resistant and will protect your concrete from mould, staining, algae, moss and repels dirt, grime and oils.

PROPERTIES

Solids (PBW): 15% plus or minus 1%

UV Light: low resistance.

Thinning: **must not!**

Application Rate: 5m²/litre/coat.

Film Build Wet: 50 microns.

Touch dry in 20-40 minutes ambient temperature dependant.

PRECAUTIONS

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period.
- Do NOT apply if rain or dew is expected within 3 hours of application.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended. Provide adequate ventilation during application and the drying period, do not apply in excessively windy conditions. Under normal conditions, the coating may require up to seven days curing to develop resin hardness.
- Please ensure coated area remains traffic free for at least three to four days.
- Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight or naked flames, Check regularly for leaks.
- Please ensure adequate ventilation, avoid breathing vapours by using Australian Standard class P1, P2 particulate respirator ensuring it is fitted correctly.
- Sealing concrete, slate, paving or slate impression concrete etc, can cause the surface to become slippery particularly when wet. We recommend the use of Prime Exposure Anti Slip (glass beads) to be applied with the sealer to reduce the risk of slipping.
- Do not use any Prime Exposure Sealers whilst smoking or near naked light or flame.

SAFETY DIRECTIONS

Keep out of reach of children. AVOID CONTACT WITH SKIN, EYES AND INHALATION OF ANY VAPOURS. Use only in well-ventilated areas. Keep containers closed when not in use. Wear overalls, safety glasses, respirator and impervious gloves when mixing and using.

APPLICATION

Check the concrete/surface is sufficiently cured and free of any excess surface moisture.

Apply coating with a xylene resistant sprayer when the surface has cured enough as not to pit or remove any cement, you can apply with a roller which will require longer curing times.

You must allow a minimum of 8 hours curing time before applying a second coat of Prime Exposure Standard Sealer.

CLEAN UP

Wash all equipment thoroughly in Prime Exposure Xylene and allow to dry.

FIRST AID INSTRUCTIONS

If affected by inhalation, move to fresh air. Call a doctor if symptoms develop or persist. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation occurs, seek medical advice. If eye contact occurs, flush eyes immediately with water. In all cases of eye contact, it is a sensible precaution to seek medical advice. If swallowed, rinse mouth thoroughly with water. Do NOT induce vomiting. Give a glass of water to drink. If vomiting occurs, give further water. Seek medical advice.

SPILLS AND DISPOSAL

It is important to keep all sealers & Solvents out of sewer and storm water drains. Do NOT pour any leftover product down the drain. If Spills occur, remove or isolate all ignition sources. Contain and absorb spill in dry, inert material such as sand. Collect in sealable containers and dispose of as trade Waste in accordance with local authority guidelines.

Retain any remaining product in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

DISCLAIMER

No responsibility can be accepted or any express or implied warranty given where performance of the product is affected by surface preparation, method of application or any other circumstances beyond the company's control.

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending or using product contained in this information as conditions and applicable laws may differ from one location to another and may change with time. Those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Prime Exposure assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Prime Exposure. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

For further information please visit www.primeexposure.com.au