



Technical Data Sheet

Prime Anti Crete

Protective Coating Against Concrete Spatter – Stops Concrete Sticking where it shouldn't

Product Overview

Prime Anti Crete is a specially formulated protective coating for equipment and surfaces exposed to wet concrete. It forms a barrier that prevents spatter from bonding, allowing clean-up to be as simple as a rinse with water. Regular use keeps tools and machinery free from build-up, reduces maintenance, and extends service life. Offering coverage of up to 40 m² per litre on smooth surfaces, it is an economical and reliable solution. Prime Anti Crete is also highly effective on Colorbond fences and surrounding windows during concrete pours, ensuring property stays protected, damage is avoided, and you get paid for a clean, professional finish.

Key Advantages

Feature	Benefit
Water rinse-off	Easily washes away with water
All-weather use	Performs in hot or cold conditions
Flexible application	Apply with spray, brush, roller, or mop
Non-corrosive	Will not damage or rust equipment
Removes build-up	Gradually loosens hardened deposits
Degreasing action	Helps release dirt and grease

Typical Applications

Prime Anti Crete is recommended for use on:

- Ready-mix concrete trucks
- Concrete finishing tools and accessories
- Screeds and formwork (backside)
- Windows, staircases, and fixtures during construction
- Colorbond fences and surrounding windows near pours

Surface Protection for Windows & Fixtures

Applying Prime Anti Crete to windows, Colorbond fences, and other smooth fixtures protects surfaces from wet concrete sticking where it shouldn't. If washed off by rain, simply reapply. When cleaned thoroughly with water, it will not affect painting or finishing.

Directions for Use

Surface Preparation

Ensure surfaces are dry and free of dust. May also be applied over light build-up.

Application

Apply evenly with sprayer, roller or brush.

Cleaning & Reapplication

Once the surface has been sprayed with Prime Anti Crete, we recommend washing it clean with a hose, brush, or pressure cleaner within 24 hours for optimal results. Depending on the surface type, the active ingredients in Prime Anti Crete may continue to provide protection for a significantly longer period. Reapply once dry if required. Daily use on tools and equipment after washdowns is recommended.

Important Notes

Do not dilute with water, diesel, or fuel oils. Dilution reduces effectiveness.

Safety & Handling

- Keep out of reach of children.
- Avoid prolonged skin contact.
- Use in well-ventilated areas.
- Refer to the SDS for full safety information before use.

Storage & Packaging

Available in 500ml spray bottles, 10LT and 20LT drums. Store in a cool, dry location. Avoid direct sunlight.